

# Steel Automatic High Speed Strapping Machine 23-1/8 In. x 48-3/8 In. x 58 In. Gray

**MODEL ASM-3123**

Packaging Equipment / High Speed Strapping Machine

## PRODUCT OVERVIEW

The high speed strapping machine is a productive solution to most polypropylene strapping tasks. The automatic arch strapping machine features the "auto-feeding" function that automatically feeds polypropylene strapping to arch and is ready for each application. The "auto-positioning" system automatically positions and secures the polypropylene strapping efficiently for each cycle. The "jam-free" feature ejects missed strap cycles and resets the unit. The user friendly controls allow the operator to choose between panel mounted controls, foot pedal, or table top ball switch. Actual production will vary depending on package size, chute size, and operator dexterity. The unit has heat welded polypropylene strapping, easy access for reloading strapping...

## KEY FEATURES

- Solution to most polypropylene strapping tasks
- Auto-feeding automatically feeds arch and is ready for each application
- Auto-positioning automatically positions and secures efficiently for each cycle
- Jam-free feature ejects missed strap cycles and resets the unit

## CORE PRODUCT DATA

**ASSEMBLED WEIGHT**  
**434 lbs**

**ASSEMBLED SIZE**  
**48.375" W x 23.125" L x 58" H**

**SHIP WEIGHT**  
**531 lbs**

**PACKAGE 1 SIZE**  
**40" W x 48" D x 67" H**

**COLOR / FINISH**  
**Gray**

**FREIGHT TYPE**  
**LTL Palletized**

**AVAILABILITY** Out of Stock - Please Contact Sales

**QUICKSHIP: YES**

Products are sold through Vestil distributor partners. Contact a distributor for current pricing and ordering.

PRODUCT SPECIFICATIONS

|                                   |        |
|-----------------------------------|--------|
| Maximum Package Width (in.)       | 29-1/4 |
| Maximum Package Height (in.)      | 22-1/2 |
| Table Top Height (in.)            | 31-1/2 |
| Maximum Cycles per Minute         | 30     |
| Voltage/Phase                     | 115/1  |
| Polypropylene Strapping (in.)     | 1/2    |
| Strap Tension Minimum (lbs.)      | 15     |
| Strap Tension Maximum (in.)       | 150    |
| Strapping Core Size Minimum (in.) | 6      |
| Strapping Core Size Maximum (in.) | 8      |
| Caster Width (in.)                | 1-1/4  |
| Caster Diameter (in.)             | 3      |
| Maximum Roll Diameter (in.)       | 16     |

PRODUCT & SHIPPING REFERENCE

Shipping Point: Angola, IN 46703

Warranty:

90 Days

AVAILABLE PRODUCT RESOURCES



SCAN FOR CURRENT PRODUCT DATA

Live product page: <https://www.vestil.com/product.php?FID=413>