

# Galvanized Steel Crossover Ladder 6 Step 23.5 In. x 36 In. 500 Lb. Capacity Silver

**MODEL COL-6-56-23-HDG**

Industrial Ladders / Galvanized Cross-Over Ladders



## PRODUCT OVERVIEW

In crowded industrial settings, sometimes the best way around an obstruction is up and over. Utilizing a crossover ladder allows the permanent pieces in the work area to stay in place while providing a more efficient option for personnel. The horizontal platform includes both upper and lower rails for complete staff security. Units must be anchored to the surface. During times of temporary use, the ladder can be knocked down for storage and shipping. Handrails have a safety yellow powder coat finish. Steps and platform have a durable hot dip galvanize finish.

## KEY FEATURES

- Serrated steps for extra grip and safety
- Meets OSHA 29 CFR 1910.23 and ANSI A14.7 standards
- Ground legs include floor mounting pads
- 58 degree climbing angle

## CORE PRODUCT DATA

**ASSEMBLED WEIGHT**  
**394 lbs**

**ASSEMBLED SIZE**  
**29.25" W x 104" L x 102.875" H**

**SHIP WEIGHT**  
**397 lbs**

**PACKAGE 1 SIZE**  
**40" W x 84" D x 32" H**

**COLOR / FINISH**  
**Silver**

**FREIGHT TYPE**  
**LTL Palletized**

**AVAILABILITY**      Quote Required - Please Contact Sales

**QUICKSHIP:** --

Products are sold through Vestil distributor partners. Contact a distributor for current pricing and ordering.

PRODUCT SPECIFICATIONS

|                             |                |
|-----------------------------|----------------|
| Uniform Capacity (lb.)      | 500            |
| Platform Height (in.)       | 60             |
| Platform Width (in.)        | 23-1/2         |
| Platform Length (in.)       | 36             |
| Handrail Height (in.)       | 42-5/8         |
| Mid-Rail (in.)              | 21             |
| Toeboard (in.)              | 4              |
| Step Width (in.)            | 23-1/2         |
| Step Depth (in.)            | 7              |
| Step Spacing (in.)          | 10             |
| Step Angle (degrees)        | 58             |
| Number of Steps             | 6              |
| Clearance Span Width (in.)  | 26-1/8         |
| Clearance Span Height (in.) | 58-1/4         |
| Overall Span Width (in.)    | 104            |
| OSHA                        | 29 CFR 1910.23 |

PRODUCT & SHIPPING REFERENCE

Shipping Point: Angola, IN 46703

Warranty: 1 Year

AVAILABLE PRODUCT RESOURCES



SCAN FOR CURRENT PRODUCT DATA

Live product page: <https://www.vestil.com/product.php?FID=489>