

# Steel Adjustable Spreader Beam 104-1/2 In Length 8,000 Lb. Capacity Blue

**MODEL SBM-80**

Overhead Lifting / Adjustable Spreader Beams

## PRODUCT OVERVIEW

The adjustable spreader beam is ideal for the manufacturing and maintenance facilities. The steel construction keeps the unit durable and strong for a lifetime of use. The beam is shipped with a test certificate.

## KEY FEATURES

- Designed to lift and move uneven and awkward loads
- Complies with ASME B30.20-1993 standards
- Includes two lower bails and one upper bail standard for added versatility
- Welded steel construction for heavy duty performance

## CORE PRODUCT DATA

ASSEMBLED WEIGHT  
**265 lbs**

ASSEMBLED SIZE  
**6" W x 104.5" L x 24.5" H**

SHIP WEIGHT  
**336 lbs**

PACKAGE 1 SIZE  
**34" W x 107" D x 12" H**

COLOR / FINISH  
**Blue**

FREIGHT TYPE  
**LTL Palletized**

**AVAILABILITY** Available

**QUICKSHIP: YES**

Products are sold through Vestil distributor partners. Contact a distributor for current pricing and ordering.

PRODUCT SPECIFICATIONS

|                                      |             |
|--------------------------------------|-------------|
| Uniform Capacity (lb.)               | 8,000       |
| Headroom (in.)                       | 20-3/4      |
| Minimum Spread (in.)                 | 8           |
| Maximum Spread (ft.)                 | 8           |
| Usable Upper Bail Width/Height (in)  | 4 x 6-3/4   |
| Usable Lower Bail Width/Height (in.) | 3 x 5-1/4   |
| Upper/Lower Bail Thickness (in.)     | 1-1/4; 1    |
| ASME                                 | B30.20-1993 |
| C-Channel Height (in.)               | 8           |
| Overall Height (in.)                 | 24-1/2      |
| Overall Width (in.)                  | 6           |
| Overall Length (in.)                 | 104-1/2     |

PRODUCT & SHIPPING REFERENCE

Shipping Point: Angola, IN 46703

Warranty:

90 Days

AVAILABLE PRODUCT RESOURCES



SCAN FOR CURRENT PRODUCT DATA

Live product page: <https://www.vestil.com/product.php?FID=572>